


RTEC L-T7515™



- 200 Industrial Washing Cycles
- Ironing, Pre-drying
- high temperature setrilization
- capable of 60 bar pressure

Environmetal Sepsifications

Operating Temperature	-30°C to +85°C
Ambient Temperature	-30°C to +110°C
IP Classification	IP68
Mechanical Resistance	60 bars
Chemical Resistance	Normal common chemicals in the washing processes
Heat Resistance	Washing: 90°C, 15 mins, 200 cycles Pre-drying: 180°C, 30 mins Ironing: 180°C, 10 sec, 200 cycles Sterilization: 135°C, 20 mins
Certifications	CE approved RoHS approved ATEX/IECEX certified
Warranty	2 years or 200 washing cycles

Mechanical Sepsifications

Tag Materials	Metal Wire
Surface Materials	Textile
Dimensions	15 x 75 x 1.5 mm
Weight	0.7 g
Color	White
Attachment	L-T7515S: Sew in the hem or woven label L-T7515P: Heat-sealing at 215°C@15 sec & 4 bars

*During sewing, the stitching thread should not damage the metal wire and chip module. During heat-sealing, recommend 215°C-218°C (15 seconds - 20 seconds).

RF Sepsifications

RF Air Protocol	EPC Global Class 1 Gen2 ISO18000-6C
Operating Frequency	UHF 866-868 MHz (ETSI) UHF 902-928 MHz (FCC)
Environment Compatibility	Optimized in Air
Read Range	Up to 6 m (off metal)
Polarization	Linear
IC Type	Impinj R6-P
Memory Configuration	EPC 128bit TID 96bit User 32bit

*Read ranges indicated in this datasheet is achieved by using our standard testing methodology. Actual performance will be different if different reader hardware and output power is applied.

Order Information

Product #	RTEC6-T7515S
Product Name	RTEC L-T7515S
Product #	RTEC6-T7515P
Product Name	RTEC L-T7515P



RTEC Singapore
57 Mohamed Sultan Road
#01-05 Sultan Link
Singapore 238997

RTEC China
L3 Enterprise accelerator B,
Scientific innovation District,
MianYang City
Sichuan, China 621000

