


RTEC Promass Micro™



- 贵重零部件
- 重要材料或物体
- 重型机械标识
- 石油天然气行业

环境参数

操作温度	-30°C to +85°C
环境温度	-30°C to +250°C
IP等级	IP68
冲击振动	MIL STD 810-F CE approved
认证	RoHS approved ATEX/IECEX certified
质保	1 year

定制化服务

写号

根据客户要求写码，包括EPC区，用户区写码等

外观

定制外观设计，如logo、一二维条码、文字PET标签等.



机械参数

标签材质	不锈钢
表面材质	PEEK
尺寸	Φ24.2 x 8.5 mm
重量	15.5 g
安装方式	工业级环氧胶 焊接
颜色	默认银色和黑色

射频参数

空中协议	EPC Global Class 1 Gen2 ISO18000-6C
操作频率	UHF 866-868 MHz (ETSI) UHF 902-928 MHz (FCC)
环境兼容	金属上最优
读取距离	3 m (金属)
极化	线极化
芯片	Impinj R6-P
存储	EPC 128bit TID 96bit User 32bit

*Read ranges indicated in this datasheet is achieved by using our standard testing methodology. Actual performance will be different if different reader hardware and output power is applied.

订购信息

Product #	RTEC4040311
Product Name	RTEC Promass Micro ETSI
Product #	RTEC4040312
Product Name	RTEC Promass Micro FCC

RTEC Singapore

57 Mohamed Sultan Road
#01-05 Sultan Link
Singapore 238997

RTEC China

L3 Enterprise accelerator B,
Scientific innovation District,
MianYang City
Sichuan, China 621000

